Kentucky Department for Environmental Protection Division of Waste Management Underground Storage Tank Branch 300 Sower Boulevard, Second Floor – Frankfort KY 40601 (502) 564-5981

FOR OFFICIAL USE ONLY-DO NOT WRITE IN THIS SPACE

UST Galvanic Cathodic Protection Evaluation						
1. UST Facility Information						
Agency Interest Number (AI)	2871					
UST Facility Name						
	Street Address: 104 E Lincolnway					
UST Facility Physical Address	City: La P	orte	County: La Port	е	Zip Code	e: 46350
2. Cathodic Protection Tester Evaluation (mark only one)						
Date of Evaluation	8 15 20	022				
	□ New Install (within 180 days) □ Re-evaluation following repair / modification (within 180 days)					
Reason for Evaluation (mark only one)	☑ Routine (every 36 months)	☐ Re-evaluation	following a failure (v	vithin 30 da	ays)
All protected structures at this UST facility pass the cathodic protection system evaluation and it is judged that adequate cathodic protection has been provided to the UST system. Complete Section 4.						
One or more protected structure at this UST f protection has not been provided to the UST			em evaluation and it i	s judged that adequa	te cathodic	; ☐ Fail
If the remote and the local potential readings do not both indicate the same test result on all protected structure (both pass or both fail), the cathodic protection system shall be re-evaluate and/or retested by a corrosion expert. Complete Section 3.						
I certify that all the information provided or	n this docume	ent is true, accurate, a	nd complete.			
Cathodic Protection Tester	Printed Seth :Lynn			Date	8 /15/2022	
Certification	Signature				Date	
Certification Type (mark all that apply)	□NACE					
Certification	Number: C	Number: CP-16644 Expiration Date: 8 /5 /2025				
Contact Information	Phone: (219	Phone: (219) 333-1648 Email: seth@midwesttanktesting.com				
Company Name	Midwest Tank Testing					
3. Corrosion Expert Evaluation (mark only one)						
The evaluation shall be conducted and/or evaluated by a corrosion expert when: a) an inconclusive is indicated for any protected structure since both the local and the remote structure-to-soil potentials do not result in the same outcome (both pass or both fail); b) repairs to galvanized or uncoated steel piping are conducted or c) supplemental anodes are added to the tanks and/or piping without following an acceptable industry code.						
Date of Evaluation	1 1					
All protected structures at this UST facility cathodic protection has been provided to the	pass the cathodic protection system evaluation and it is judged that adequate UST system. Complete Section 4.					
	One or more protected structure at this UST facility fail the cathodic protection system evaluation and it is judged that adequate cathodic protection has not been provided to the UST system. Complete Section 5.				ail	
I certify that all the information provided on this document is true, accurate, and complete.						
	Printed				Doto	1 1
Corrosion Expert Certification	Signature				Date	
	License #			License Expiration	on Date	1 1

AI <u></u>							
4. Applicable Evaluation Criteria (mark all that apply)							
	Structure-to-soil potential more negative than -850mV with respect to a Cu/CuSO ₄ reference electrode with the protective current applied. Applicable to any galvanically protected structure.					0 On	
Structure to sail notabilel many negative than 950mV/with respect to a CV/CVCO reference electrode with the protective gurrent					□ 85	□ 850 Off	
Structure disconnec		least 100mV of catho	dic polarization. Applicable to	galvanic systems where anode	es can be	□ 10	0 mV Polarization
			5. Required Action	ns (mark only one)			
			necessary at this time. Next ever eason for Evaluation) occurs.	valuation due 3 years from the o	date of this	√ No	one
				termine if passing results can be		□Re	e-evaluation
Cathodic p	protection is not ad	equate. A repair or mod	ification is necessary as soon as	s practical, but within the next 90) days.	Re	epair & Re-evaluation
Next Cath	nodic Protection	Evaluation shall be o	completed by / /				
			6. Description of Eva	luated UST System			
Tank	Product	Capacity (gal)	Tanks	Piping	Flex Connectors		Connectors
	1100001	Capacity (gaily	ramo	pg	STF	כ	UDC
1	Regular	10k	STIP3	FRP	SS FLE	ΞX	SS FLEX
2	Premium	10k	STIP3	FRP	BOOTI	ED	BOOTED
3							
4							
5							
6							
		7. Description	of Cathodic Protection Sys	stem Repairs and/or Modif	ications		
Provide detailed information about all modifications or repairs made to the cathodic protection system. Provide a detailed drawing below of the UST facility and cathodic protection systems. Sufficient detail shall be given in order to clearly indicate where the reference electrode was placed for each structure-to-soil potential that is recorded on the survey forms. At a minimum indicate the following: a) Tanks b) Piping c) Dispensers e) Anodes and Wires b) Piping c) Dispensers g) Each reference electrode placement (indicated by a code: 1, 2, T-1, T-2) corresponding with the appropriate line number in Section 9.							
d) Buildings and Streets Supplemental anodes for metallic pipe (attach corrosion expert's design or documentation that industry standard was followed).							
□ Supplemental anodes for a sti-P³® tank (attach corrosion expert's design or documentation that industry standard was followed).							
Galvanically protected tanks/piping not electrically isolated (explain in "Remarks/Other" below).							
Remarks/Other							
Detailed Drawing							

Use this s	8. Galvanic (a ection to document measu	Sacrificial Anode) Cath rements of continuity on US	nodic Protection System ST systems that are protect	m Continuity Survey ed by galvanic cathodic pro	otection systems.
Structure "A"1	Structure "B" ²	Structure "A" Fixed Remote Voltage ³	Structure "B" Fixed Remote Voltage ⁴	Point-to-Point Fixed Remote Voltage ⁵	Isolated / Continuous / Inconclusive ⁶
Premium Tank Bottom	Premium Tank Fill Riser	-921 mV	-915 mV		Inconclusive
Premium Tank Bottom	Premium Tank Fill Riser			17 mV	Isolated
Regular Tank	Fill Riser	-930 mv	-199 mv		Isolated
	ATG Riser		-374 mv		Isolated
	STP		-398 mv		Isolated
Premium Tank	Fill Riser	-1003 mv	-461 mv		Isolated
	ATG Riser		-382 mv		Isolated
	STP		-362 mv		Isolated
Comments					

¹ Describe the cathodically protected structure being demonstrated as isolated from unprotected structures (e.g. premium tank bottom).

² Describe the unprotected structure being demonstrated as isolated from the protected structure (e.g. premium tank fill riser).

³ Record the measured structure-to-soil potential of the cathodically protected structure "A" in millivolts (e.g. -921 mV).

⁴ Record the measured structure-to-soil potential of the unprotected structure "B" in millivolts (e.g. -915 mV).

Record the voltage observed between the protected and the unprotected structures when conducting point-to-point testing (e.g. 17 mV).
 Document whether the test (fixed cell and/or point-to-point) indicated the protected structure was isolated, continuous or inconclusive.



	Use this section to do		cial Anode) Cathodic Prote c cathodic protection system by			rements.
Location Code ⁷	Structure ⁸	Contact Point ⁹	Local Reference Cell Placement ¹⁰	Local Voltage ¹¹	Remote Voltage ¹²	Pass / Fail / Inconclusive ¹³
Example 1	Plus Tank	Tank Bottom	Plus Tank STP Manway	-928 mV	-810 mV	Inconclusive
Example 2	Plus Piping	Dispenser 5/6	Under Dispenser 5/6	-890 mV	-885 mV	Pass
	Regular	Tank Bottom	Fill End	-1035 mv		PASS
			ATG Center	-1019 mv		PASS
			STP End	-1014 mv		PASS
	Premium	Tank Bottom	Fill End	-911 mv		PASS
			ATG Center	-955 mv		PASS
			STP End	-1048 mv		PASS
Comments						
facility record	ds please visit <u>http://eec.</u> l	it this form please contact the (y.gov/pages/openrecords.as	e cabinet at (502) 564-5981 or vi px or email <u>EEC.KORA@ky.gov</u>	sit out web site at <u>fill</u> <u>/</u> .	p.//waste.ky.gov/ust.	For copies of UST

⁷ Designate numerically or by code on the site drawing each local reference electrode placement (e.g. 1, 2, 3..., T-1, T-2..., P-1, P-2...etc.).

B Describe the structure that is being tested (e.g. plus tank, premium piping, flex connector, etc.).

Describe where contact with the structure that is being tested is made (e.g. plus tank @ test lead, diesel piping @ dispenser 5/6, etc.)

Describe the exact location where the reference electrode is placed for each "local" measurement (e.g. soil @ plus tank STP, soil @ dispenser 5/6, etc.).

Record the structure-to-soil potential measured with the reference electrode place "local" in millivolts (e.g. -865 mV).

¹² Recorded the structure-to-soil potential measured with the reference electrode placed "remote" (copy voltage that was obtained during continuity survey).

¹³ Indicate whether the tested structure passed or failed the -850 mV "on" criterion based on the interpretation of the test data.



Cathodic Protection Test - Site Diagram with Drill Holes & Helium Hits **CP** Diagram

316 W. Indiana Ave.

Chesterton, IN 46304

Test Location Information				
Name and FID #	FID # 2871			
Address	104 E Lincolnway			
City/State/Zip	Laporte IN 46350			

Test Date				
Testing Company Information				
Name	Midwest Tank Testing			
Address	316 W. Indiana Ave.			
City/State/Zip	Chesterton, IN 46304			
Phone	800-975-1436			
Tech Name	Seth Lynn			
Cert #	CP-16655			

