

## APPENDIX C-5 UT OVERFILL EQUIPMENT INSPECTION AUTOMATIC SHUTOFF DEVICE AND BALL FLOAT VALVE

TEST DATE:	10/10/2023	OWNER NAME:	New Punjab LLC
LOCATION NAME:	Midwest Petro	OWNER ADDRESS:	29026 State Road 20
LOCATION ADDRESS:	29026 State Road 20	OWNER CITY/STATE/ZIP:	Elkhart, IN 46517
LOCATION CITY/STATE:	Elkhart, IN 46517		
LOCATION PHONE:	317-645-0215	LOCATION FID#:	25595
LOCATION CONTACT:	Tanks Data / Virendar Kumar	WORK ORDER NO:	NE-0761

Product Grade	RUL 1 11608	PUL 2 3765	3 6044	<b>KER</b> 4 3765		
Tank Number						
Tank Volume, gallons						
Tank Diameter, inches	90"	90"	90"	90"		
Overfill Prevention Device Brand	FRANKLIN	FRANKLIN	FRANKLIN	FRANKLIN		
Туре	Automatic Shutoff Valve	Automatic Shutoff Valve	Automatic Shutoff Valve	Automatic Shutoff Valve	-	-
AUTOMATIC SHUTOFF DEVICE INSPECTION						
Drop tube removed from tank?	YES	YES	YES	YES		
2. Drop tube and float mechanisms free of debris?	YES	YES	YES	YES		
3. Float moves freely without binding and poppet moves into flow path?	YES	YES	YES	YES		
4. Bypass valve in the drop tube open and fress of blockage (if present)?	NOT PRESENT	NOT PRESENT	NOT PRESENT	NOT PRESENT		
5. Flapper adjusted to shut off flow at 95% capacity?*	YES	YES	YES	YES		
BALL FLOAT VALVE INSPECTION **						•
Tank Top fitting vapor-tight and leak-free?						
2. Ball float cage free of debris?						
3. Ball free of holes an dcarcks and moves freely in cage?						
4. Vent hole in pipe open and near top of tank?						
5. Ball float pipe proper length to restrict flow at 90% capacity?***						
A "No" to any item in Lines 1-5 indicates a test failu	ıre.					•
AUTO SHUT OFF DEVICE TEST RESULTS	PASS	PASS	PASS	PASS		
BALL FLOAT VALVE INSPECTION RESULTS						

<sup>\*</sup> Use manufacturer's suggested procedure for determining if automatic shutoff device will shut off flow at 95% capacity.

O
SERVICE TECHNICIAN NAME (printed)
ADAM WILDER
CERTIFIED TECHNICIAN NAME (printed)

SERVICE TECHNICIAN SIGNATURE

**CERTIFIED TECHNICIAN SIGNATURE** 

UC112310

EXPIRATION DATE: 01/23/2025

CERT NO:

<sup>\*\*</sup> If a ball float is found to fail in inspection, another method of overfill must be used.

<sup>\*\*\*</sup> Use manufacturer's suggested procedure for determining if flow restriction device will restrict flow at 90% capacity.